

TESA® YR Precision Dial Gauges 40 mm Dial Diameter, 0,01 mm Reading

Precision mechanism with both a ground toothed rack made from hardened stainless steel and sturdy gear drive.

- Regular models and models IP 54 protected against the penetration of liquids, with or without central lug back.



DIN 878
NF E 11-050
ISO/R 463

0,01 mm

2,2 mm

Rotating dial.
Regular models with dial lock.

Full-metal case housing

Fixing shank and plunger in hardened stainless steel

High performance shockproof system in both directions

Adjustable tolerance markers

M2,5 thread for the measuring insert

Accuracy: see table on page E-10

See table on page E-10

3 mm dia. ball tip already mounted

Cardboard box

Identification number

Inspection report with a declaration of conformity

No	mm	mm	mm		mm		
Regular models							
14.10210	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 50	can be locked
14.10211	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 0	can be locked
14.10212	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 50	
Models IP54 protected against the penetration of liquids							
14.10320	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 50	
14.10321	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 0	
Models IP54 protected against the penetration of liquids, with central lug back							
14.10322	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 50	
14.10323	0,01	5	5,4	with	0,5	0 ÷ 25 ÷ 0	

