

TESA® YR Precision Dial Gauges 57 or 58 mm Dial Diameter, 0,001 mm Reading

Feature a precision movement based on a combined gear and level transmission – This combination similar to that of precision indicators offers full shock protection as well as very low hysteresis errors.

- Regular models and models IP54 protected against the penetration of liquids, with or without central lug back.



DIN 878
NF E 11-050
ISO/R 463

0,001 mm

1,5 mm

Rotating dial.
Regular models with dial lock.

Full-metal case housing

Fixing shank and plunger in hardened stainless steel

High performance shockproof system in both directions

Adjustable tolerance markers

M2,5 thread for the measuring insert

Accuracy: see table on page E-10

See table on page E-10

3 mm dia. ball tip already mounted

Cardboard box

Identification number

Inspection report with a declaration of conformity



Regular models

14.10410	0,001	1	3,3	57	with	0,1	0 ÷ 50 ÷ 100	can be locked
14.10411	0,001	1	3,3	57	with	0,1	0 ÷ 50 ÷ 0	can be locked

Models IP 54 protected against the penetration of liquids

14.10520	0,001	1	3,3	58	with	0,1	0 ÷ 50 ÷ 100
14.10521	0,001	1	3,3	58	with	0,1	0 ÷ 50 ÷ 0

Models IP54 protected against the penetration of liquids, with central lug back

14.10522	0,001	1	3,3	58	with	0,1	0 ÷ 50 ÷ 100
14.10523	0,001	1	3,3	58	with	0,1	0 ÷ 50 ÷ 0

