

TESA® YR Precision Dial Gauges 57 or 58 mm Dial Diameter, 0,01 mm Reading

Precision mechanism with both a ground toothed rack made from hardened stainless steel and sturdy gear drive.

- Regular models and models IP 54 protected against the penetration of liquids, with or without central lug back.



DIN 878
NF E 11-050
ISO/R 463



0,01 mm



1,5 mm



Rotating dial.

Regular models with dial lock.



Full-metal case housing

Fixing shank and plunger in hardened stainless steel



High performance shockproof system in both directions



Adjustable tolerance markers

M2,5 thread for the measuring insert



Accuracy: see table on page E-10



See table on page E-10



3 mm dia. ball tip already mounted



Cardboard box



Identification number



Inspection report with a declaration of conformity



Regular models

14.10610	0,01	10	10,5	57	with	1	0 ÷ 50 ÷ 100	can be locked
14.10611	0,01	10	10,5	57	with	1	0 ÷ 50 ÷ 0	can be locked
14.10612	0,01	10	10,5	57	with	1	0 ÷ 50 ÷ 100	

Models IP54 protected against the penetration of liquids

14.10720	0,01	10	10,5	58	with	1	0 ÷ 50 ÷ 100	
14.10721	0,01	10	10,5	58	with	1	0 ÷ 50 ÷ 0	

Models IP54 protected against the penetration of liquids, with central lug back

14.10722	0,01	10	10,5	58	with	1	0 ÷ 50 ÷ 100	
14.10723	0,01	10	10,5	58	with	1	0 ÷ 50 ÷ 0	

